

# Canon



PRODUCTION SOLUTIONS



 **imageRUNNER®**  
7105

**meap**  
POWERED BY 

## CHALLENGE YOUR DOCUMENT PRODUCTION STANDARDS

The Canon imageRUNNER 7105 is perfectly suited for central reproduction departments, print-for-pay establishments, print-on-demand applications, and large corporate offices where high-speed document production is required. To maximize versatility, the system is designed to meet professional publishing needs with available in-line perfect bookbinding, saddle-stitched booklet finishing, hole-punching, tab-feeding, and high-capacity stacking.

You can also leverage your imageRUNNER device investment further by using part of the system's vast memory as an on-site document storage and print-on-demand solution, while retaining complete control over device access and data protection with the latest identity management and security measures.

### MAIN UNIT

Type:	Digital Multifunctional Imaging System
Imaging System:	Laser Dry Electrostatic Transfer
Developing System:	Dry Monocomponent Toner Projection
Main Unit CPU:	Dual Canon Custom Processors
Interface Connection:	10/100Base-TX (RJ-45), USB 2.0 High Speed
Image Server Memory:	Standard 1GB RAM + 40GB HDD
Max. Mail Boxes Supported:	100 (Max. Page Capacity: Approximately 20,000 pages)
Max. Copy Reservation:	20 Jobs
Acceptable Originals:	Sheets, Books, 3-Dimensional Objects up to 4.4 lb.
Max. Original Size:	11" x 17"
Max. Copy Size:	11" x 17"
Min. Copy Size:	3-15/16" x 5-7/8" (Stack Bypass)
Scanning Resolution:	600 x 600 dpi
Copy Resolution:	1200 x 600 dpi (Interpolated)
Halftone:	256-Level Grayscale
Exposure Control:	Automatic or Manual (Text, Photo, or Text/Photo)
Copy Speed:	105 cpm (Letter) 53 cpm (11" x 17")
First-Copy Time:	2.8 Seconds (From Platen)
Warm-Up Time:	6 Minutes or Less
Multiple Copies:	1 – 9,999
Duplexing:	Standard Automatic Trayless Duplexing
Magnification	
From Glass:	25% - 400% (In 1% increments)
From Feeder:	25% - 200% (In 1% increments)
Preset Reduction:	25%, 50%, 64%, 73%, 78%
Preset Enlargement:	121%, 129%, 200%, 400%
Standard Paper Supply:	Dual Front-Loading Drawers (1,500 Sheets each) Dual Front-Loading Cassettes (550 Sheets each) 50-Sheet Stack Bypass
Optional Paper Supply:	3,500-Sheet Paper Deck-W1/X1
Paper Capacity:	Standard: 4,150 Sheets Maximum: 7,650 Sheets

Acceptable Paper Weight:	17 lb. Bond to 110 lb. Index (All Sources)
Power Consumption:	2.15kW
Plug:	NEMA 6-15R
Photoconductor Yield:	6 Million Impressions
Toner Yield:	47,000 Images @ 6% Coverage
<b>Duplex Automatic Document Feeder</b>	
Tray Capacity:	100 Sheets
Scanning Speed:	85 Sheets Per Minute (Letter)
Acceptable Original Sizes:	Statement to 11" x 17"
Acceptable Size Originals:	Same Width
Acceptable Paper Weight:	13 lb. Bond to 80 lb. Cover

### OPTIONAL ACCESSORIES

<b>Paper Deck-W1/Paper Deck-X1</b>	
Paper Capacity:	3,500 Sheets
Number of Drawers:	1
Acceptable Paper Weight:	17 lb. Bond to 110 lb. Index
Acceptable Paper Size	
Paper Deck-W1:	Letter
Paper Deck-X1:	Letter-R, Letter, Legal, 11" x 17"
<b>Perfect Binder-A1*</b>	
Bind Method:	Perfect Binding
Cutting Method:	Stack Rotation 3-Direction, or 1-Direction (for Open Edge) Cut
Finished Book Size: (After 3-Direction Cutting)	
Width:	7-1/8" to 11-1/4"
Length:	5-5/8" to 8-1/4"
Book Thickness:	10 to 200 Sheets Using 17 to 24 lb. Bond 10 to 150 Sheets Using 24 to 28 lb. Bond 10 Sheets Using 28 lb. Bond to 110 lb. Index
Cover Source Location:	Stack Bypass, Paper Drawers, Paper Deck (Imageable) Document Insertion Unit (For Pre-Printed Covers)
Stacker Tray Capacity:	3.94" (100mm) (Equivalent to 10 100-page Books with 17 lb. Bond)

Glue Supplies & Yield:	Glue-A1 (33 lb./15kg): Estimated Yield: 5,000 Sets of 100 Sheet Books (20 lb. Bond) Glue-A2 (11 lb./5kg): Estimated Yield: 1,650 Sets of 100 Sheet Books (20 lb. Bond)
Glue Warm-Up Time:	380 Seconds or Less
Glue Unit Capacity:	Bind Approximately 180 100-page Books Using 20 lb. Bond Paper
Trim Range	
Width:	7mm – 27mm
Length:	7mm – 39mm Adjustable in 1mm increments
Trimmer Waste Capacity:	Space for 3-Sided Cuttings From Approximately 15 100-page Books

### Document Insertion Unit (Standard With Perfect Binder-A1)

Acceptable Media:	Covers and Inserts
Number of Trays:	2
Tray Capacity	
Upper Tray:	200 Sheets (20 lb. Bond)
Lower Tray:	200 Sheets (20 lb. Bond)
Acceptable Paper Weight:	17 lb. Bond to 158 lb. Index
Acceptable Paper Sizes	
Upper Tray:	Letter, Letter-R, Executive
Lower Tray:	11" x 17", Legal, Letter, Letter-R, Executive

### Finisher-V1/Saddle Finisher-V2

Number of Trays:	2/3
Tray Capacity	
Top Tray:	3,000 Sheets
Lower Tray:	2,000 Sheets
Saddle-Stitch Tray:	30 Booklets or Limitless
Acceptable Paper Weight	
Finisher-V1:	17 lb. Bond to 110 lb. Index
Saddle Finisher-V2:	17 lb. Bond to 110 lb. Index
Acceptable Paper Size:	11" x 17", Legal, Letter, Letter-R, Statement-R, Executive
Staple Positions:	Corner Stapling, Double Stapling
Max. Stapling Capacity:	100 Sheets (Letter, Executive) 50 Sheets (11" x 17", Legal, Letter-R)
Type of Staple:	Staple-N1 (5,000 x 3)



### Device Dimensions and Power Requirements Chart

Product/Accessory Name	Dimensions (H x W x D)	Weight	Power
Main Unit	58" x 47-7/8" x 30-7/8" (1474mm x 1216mm x 783mm)	617 lb. (280kg)	208V, 60Hz, 12A
Paper Deck-W1	22-1/2" x 12-3/4" x 23" (570mm x 323mm x 583mm)	90.4 lb. (41kg)	Directly From Main Unit
Paper Deck-X1	22-5/8" x 23-3/8" x 24-1/2" (574.5mm x 593mm x 621mm)	101 lb. (46kg)	
High-Capacity Stacker-A1	48-9/10" x 33-9/10" x 30-1/5" (1240mm x 860mm x 765mm)	440 lb. (200kg)	120V, 10A
Perfect Binder-A1	53-1/2" x 36-1/4" x 31-1/8" (1360mm x 920mm x 791mm)	696 lb. (316kg)	208V, 15A
Finisher-V1	46-1/2" x 31-1/2" x 31-1/4" (1180mm x 800mm x 792mm)	278 lb. (126kg)	Directly From Main Unit* or 208V, 60Hz, 12A**
Saddle Finisher-V2	46-1/2" x 31-1/2" x 31-1/4" (1180mm x 800mm x 792mm)	392 lb. (178kg)	
Document Insertion Unit-C1	8-3/8" x 24-5/8" x 26-1/4" (213mm x 625mm x 667mm)	37.5 lb. (17kg)	From Finisher-V1 or Saddle Finisher-V2
Paper Folding Unit-D1	41" x 7-1/8" x 31" (1040mm x 179mm x 786mm)	97 lb. (44kg)	
Booklet Trimmer-C1	41" x 62-1/10" x 30-2/5" (1040mm x 1575mm x 770mm)	335 lb. (152kg)	
Professional Puncher-A1	38-1/2" x 12" x 28-1/2" (978mm x 305mm x 723mm)	170 lb. (77kg)	

\* When Finisher is equipped with Paper Folding Unit-D1 and/or Document Insertion Unit-C1.

\*\* When Finisher is equipped with Professional Puncher-A1, Booklet Trimmer-C1, High-Capacity Stacker-A1, and/or Perfect Binder-A1.

**Canon**  
image*ANYWARE*

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows and Windows NT are registered trademarks and Windows Vista is a trademark of Microsoft Corporation in the United States and/or other countries. Adobe and PostScript are registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Macintosh is a registered trademark of Apple Computer, Inc. Intel and Celeron are registered trademarks of Intel Corporation. Novell and NetWare are registered trademarks of Novell, Inc. in the United States and other countries. Solaris and Sun are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries. EFI and Command WorkStation are registered trademarks and FreeForm is a trademark of Electronics for Imaging, Inc. in the U.S. Patent and Trademark Office and certain other foreign jurisdictions. eCopy ShareScan is a trademark of eCopy, Inc. CANON, IMAGERUNNER and MEAP are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain countries. IMAGEANYWARE is a trademark of Canon. All referenced product names and other marks are trademarks of their respective owners. Specifications subject to change without notice. ©2007 Canon U.S.A., Inc. All rights reserved.

1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Plaza  
Lake Success, NY 11042

